Coated Accessories

Grindwell Norton offers a range of accessories to suit popular machine sizes and optimize performance of Norton and Grindwell Norton coated abrasive products.

Industry	Primary Auto	Auto After	Composites & Rubber
Usage	•	•	•
Direct Use	 Probable Use 		



TYPICAL APPLICATIONS

- **AUTOMOTIVE PAINT SHOPS**
 - Defect Sanding
- AUTOMOTIVE WELD & PRESS SHOPS
 - Braze smoothening
 - Light deburring and finishing

NORTON PSA Back-up Pads

Soft density low profile pads utilize 1/2" thick foam for fine finish sanding and offer moderate conformability to contours and curves. They are available with either PSA (vinyl) or Velcro (hook and loop) faces. Both designs are shock resistant and have a fiberglass backing plate with a riveted 5/16" - 24 threaded shank for added strength and increased heat resistance. They are also available with a standard 5-hole pattern for vacuum assist sanding. These pads are popular for both wood-working and automotive applications and are designed to suit all popular models of pneumatic orbital sanders.

PRODUCT OFFERINGS

- PSA Back-up Pads
- Velcro Back-up Pads
- Back-up Pads for Fibre Dsics





NORTON PSA BACK-UP PADS

FEATURES

- Special Vinyl facing
- Industry standard thread

BENEFITS

- Helps adhesion of disc yet facilitates easy removal
- Compatible with all popular machines

NORTON Velcro Back-up Pads

Designed with medium density polyurethane foam and a tapered edge for conformability, these pads are firm enough for flat surfaces, yet soft enough for severe curves and contours. Available with Velcro (hook and loop) faces in vacuum or non-vacuum. The vacuum design is available in standard 5-hole or 6-hole pattern.



NORTON VELCRO BACK-UP PADS		
FEATURES	BENEFITS	
Special hook facing	Strong holding and easy removal of discs	
Industry standard thread	Compatible with all popular machines	




STOCK AVAILABILITY TABLE

Backup Pads

Size OD x THREAD	ТҮРЕ	STOCK LIST NO.
125 mm x 5/16 - 24 TPI	PSA–VACUUM (5 Holes)	BP 1005
125 mm x 5/16 - 24 TPI	PSA-NON VACUUM	BP 1006
125 mm x 5/16 - 24 TPI	VELCRO-NON VACUUM	BV 1009
125 mm x 5/16 - 24 TPI	VELCRO-VACUUM (5 Holes)	BV 1010
150 mm x 5/16 - 24 TPI	VELCRO-VACUUM (5 Holes)	

Back-up Pads for Fibre Discs

These pads are made from proprietary thermoplastic rubber compounds that provide consistent properties over a wide range of temperatures. They are ideal pads for general purpose applications using resin fiber discs with grits 36 and finer. All pads are for discs with 7/8" holes.





STOCK AVAILABILITY TABLE

Backup Pads for Fibre Discs

Size OD x THREAD	ТҮРЕ	
4" x 5/8 – 11	Medium Density smooth face, 15,000 rpm max	
5" x 5/8 – 11	Medium Density smooth face, 12,000 rpm max	
5" x 5/8 – 11	Medium Density smooth face, 8,500 rpm max	
125 mm x 5/16 - 24 TPI	VELCRO - VACUUM (5 Holes)	